

## 1002

3 Ply Flush EcoCell™ Core



Model	1002-HE			
Thickness	13/4"			
Maximum Size	Non-Rated	Neutral Pressure (UL10B)	Positive Pressure Cat. A (UL10C)	Positive Pressure Cat. B (UL10C)
Singles	4'x9'	N/A	N/A	N/A
Pairs	8'x9'	N/A	N/A	N/A
Double Egress	N/A	N/A	N/A	N/A
Temp. Rise Rating	N/A			
Standards	Meets or exceeds WDMA I.S1A			
Faces	GrainArt™, Primed HDF, Raw HDF			
Adhesive Bond	Type 1 Crosslinked PVA			
Core Material	Rigid EcoCell $^{\rm M}$ Honeycomb with minimum crush resistance of 2500 lb/ ${\rm ft^2}$			
Core/ Edge Interface	Non Bonded			
Stiles HE	3/8" Hardwood outer stile (before trim) bonded to a 1" Structural Composite Lumber inner stile			
Rails Top & Bottom	1 3/8" Structural Composite Lumber (before trim)			
Mid	4 5/8" Structural Composite Lumber			
Lites & Louvers	Per machining sheets provided at time of order			
Machining	Per machining sheets and hardware manufacturer's templates provided at time of order			
Recycled & Renewable Content	Please contact factory			
Weight	2.11 lb/ft <sup>2</sup> *			
Warranty	Two year limited warranty for interior use, see limited warranty for details			
*Based on 3'x7' door leaf without additional blocking.				