

3454

3 Ply Flush SCL Core
45 Min. Fire Rated



Model	3454-HE			
Thickness	1 3/4"			
Maximum Size	Non-Rated	Neutral Pressure (UL10B)	Positive Pressure Cat. A (UL10C)	Positive Pressure Cat. B (UL10C)
Singles	N/A	4'x8'	4'x8'	4'x8'
Pairs	N/A	N/A	N/A	N/A
Double Egress	N/A	N/A	N/A	N/A
Temp. Rise Rating	Max. 250°F @ 30 Min.			
Standards	Meets or exceeds WDMA I.S.-1A			
Faces	GrainArt™, Primed HDF, Raw HDF			
Adhesive Bond	Type 1 Crosslinked PVA			
Core Material	Structural Composite Lumber			
Core/ Edge Interface	Bonded			
Stiles	HE	3/8" Hardwood outer stile (before trim) bonded to a 1" Structural Composite Lumber inner stile		
Rails	1 3/8" Structural Composite Lumber (before trim)			
Lites & Louvers	Per machining sheets provided at time of order			
Machining	Per machining sheets and hardware manufacturer's templates provided at time of order			
Recycled & Renewable Content	Please contact factory			
Weight	5.89 lb/ft ² *			
Warranty	One year limited warranty for interior use, see limited warranty for details			

*Based on 3'x7' door leaf.