

5 Ply Flush Agrifiber Particleboard Core
45-60 Min. Fire Rated



Models	5455-HE, 5455-LE			
Thickness	1 3/4"			
Maximum Size	Non-Rated	Neutral Pressure (UL10B)	Positive Pressure Cat. A (UL10C)	Positive Pressure Cat. B (UL10C)
Singles	N/A	4'x9'	4'x9'	4'x9'
Pairs	N/A	8'x9'	8'x9'	8'x9'
Double Egress	N/A	8'x9'	8'x9'	8'x9'
Temp. Rise Rating	Max. 250°F @ 45 Min.			
Standards	Meets or exceeds WDMA I.S.-1A			
Faces	HPL, Domestic & Exotic Wood Veneer			
Adhesive Bond	Type 1 Crosslinked PVA			
Core Material	Agrifiber Particleboard (ANSI A208.1)			
Core/ Edge Interface	Bonded			
Stiles	HE	3/8" Hardwood outer stile (before trim) bonded to a 2" Mineral Composite inner stile		
	LE	1/2" Hardwood outer stile (before trim) bonded to a 2" Mineral Composite inner stile laminated with HPL or veneer to match faces		
Rails	1/2" Hardwood outer rail (before trim) bonded to a 2" Mineral Composite inner rail			
Lites & Louvers	Per machining sheets provided at time of order			
Machining	Per machining sheets and hardware manufacturer's templates provided at time of order			
Recycled & Renewable Content	Please contact factory			
Weight	6.08 lb/ft ² *			
Warranty	Lifetime warranty for interior use, see limited warranty for details			

*Based on 3'x7' door leaf without additional blocking.