

## 7203L

Flush Radiation Shielding Particleboard Core  
1/16" - 1/8" Lead Lined  
20 Min. Fire Rated



Model	7203L-LE			
Thickness	1 3/4"			
Maximum Size	Non-Rated	Neutral Pressure (UL10B)	Positive Pressure Cat. A (UL10C)	Positive Pressure Cat. B (UL10C)
Singles	4'x8'	4'x8'	4'x8'	4'x8'
Pairs	8'x8'	8'x8'	8'x8'	8'x8'
Double Egress	N/A	N/A	N/A	N/A
Temp. Rise Rating	N/A			
Standards	Meets or exceeds WDMA I.5-1A			
Faces	HPL, Domestic & Exotic Wood Veneer			
Adhesive Bond	Type 1 Crosslinked PVA			
Core Material	LD-2 Particleboard (ANSI A208.1)			
Shielding Material	99.9 Pure Lead (ASTM B749) 1/16" - 1/8" overall thickness			
Core/ Edge Interface	Bonded			
Stiles	LE	1 3/8" Structural Composite Lumber (before trim) laminated with HPL or Veneer to match faces		
Rails	Top	6" Structural Composite Lumber (before trim)		
	Bottom	2 1/2" Structural Composite Lumber (before trim)		
Lites & Louvers	Lites should be supplied by factory, Louvers are not permitted.			
Machining	Per machining sheets and hardware manufacturer's templates provided at time of order. Continuous hinges required for warranty			
Hardware	Hinges and lead-lined hardware (locks, closers, auto door bottom, etc.) can be supplied by factory			
Recycled & Renewable Content	Please contact factory			
Weight	LL 1/16"	9.80 lb/ft <sup>2</sup> *		
	LL 1/8"	13.30 lb/ft <sup>2</sup> *		
Warranty	One year limited warranty for interior use, see limited warranty for details			

\*Based on 3'x7' door leaf.