

## 7456L / 7606L

Flush Radiation Shielding Mineral Core  
 1/16" - 1/8" Lead Lined  
 45-60 Min. Fire Rated



Models	7456L-LE, 7606L-LE			
Thickness	1 3/4"			
Maximum Size	Non-Rated	Neutral Pressure (UL10B)	Positive Pressure Cat. A (UL10C)	Positive Pressure Cat. B (UL10C)
Singles	4'x8'	4'x8'	4'x8'	4'x8'
Pairs	8'x8'	8'x8'	8'x8'	8'x8'
Double Egress	N/A	N/A	N/A	N/A
Temp. Rise Rating	N/A			
Standards	Meets or exceeds WDMA I.S.-1A			
Faces	HPL, Domestic & Exotic Wood Veneer			
Adhesive Bond	Type 1 Crosslinked PVA			
Core Material	Noncombustible Mineral Composite			
Shielding Material	99.9 Pure Lead (ASTM B749) 1/16" - 1/8" overall thickness			
Core/ Edge Interface	Bonded			
Stiles	LE	1/2" Hardwood outer stile (before trim) bonded to a 5" Mineral Composite inner stile laminated with HPL or veneer to match		
Rails		1/2" Hardwood outer rail (before trim) bonded to a 5" Mineral Composite inner rail. Top rail laminated with HPL or Veneer to match		
Lites & Louvers	Lites should be supplied by factory, Louvers are not permitted.			
Machining	Per machining sheets and hardware manufacturer's templates provided at time of order. Continuous hinges required for warranty			
Hardware	Hinges and lead-lined hardware (locks, closers, auto door bottom, etc.) can be supplied by factory			
Recycled & Renewable Content	Please contact factory			
Weight	LL 1/16"	9.90 lb/ft <sup>2</sup> *		
	LL 1/8"	13.40 lb/ft <sup>2</sup> *		
Warranty	One year limited warranty for interior use, see limited warranty for details			

\*Based on 3'x7' door leaf.